

| | | | |
|---------------------|-------------------------------|--|--------------------------|
| Installation manual | Model: SUZUKI SX 4/ Vitara | Skid plate for: engine bay and transmission case | Article: 23.2514/23.2515 |
| Body type: | Years: 2013 -/2015 - | Engine type: 1,6 AT | |

APPLICATION:

Protection of engine bay and transmission elements from mechanical deformation.
Protection of engine bay and transmission elements from dust and damp.

INSTALLATION:

Engine bay and transmission elements skid plate has been designed particularly for a certain vehicle. It should be mounted according to the producer's installation instruction by a dedicated dealer or on certified service stations. The skid plate is fixed to regular apertures located on vehicle's body load-bearing elements. In case of correct installation the skid plate should not interfere with any vehicle's units and components.

INSTALLATION MANUAL:

1. Loosen by one bolt with each side mount towing lugs.
2. Install the brackets "1" of the skid plate under the loose bolts and tighten them.
3. Fix clamp "2" on the subframe's rear part apertures of the front axle beam.
4. Fix the skid plate to the mounted parts.
5. Tighten all screw joints.

OPERATING CONDITIONS:

Engine bay and transmission elements skid plate has been designed to operate in conditions specified by vehicle's producer. Cases of crush or driving into obstacles at a speed should be excluded during exploitation. In case of head-on crush it is necessary to assure in absence of damages of vehicle's components and units and availability of roadworthiness on certified service stations.

WARRANTY:



Warranty period - 24 months.

WARRANTY TERMS:

The skid plate should be installed on a vehicle with undamaged body and load-bearing elements (vehicle, which had never been involved in road traffic accident);
There are no mechanical damages of the skid plate resulting from crush or driv All requirements to skid plate installation should be satisfied;
There are no mechanical damages of powder coating.
Producer does not bear liability for damages caused to the vehicle, health and life of people in case of installation and exploitation terms violation. Producer has a right to introduce changes into the skid plate construction.

ENVIRONMENTAL PROTECTION

Dispose of packaging properly. It is recommended to take it for recycling. Don't forget about environmental protection.



LIST OF PARTS

| NO. | NAME | QTY. |
|-----|-------------|------|
| 1 | Bracket | 2 |
| 2 | Clamp | 2 |
| 3 | Bolt M10x30 | 4 |
| 4 | Washer 10 | 4 |

| Thread | M6x1.0 | M8x1.25 | M10x1.5 | M12x1.75 |
|-------------------|--------|---------|---------|----------|
| Tightening torque | 9.8 Nm | 24.0 Nm | 47.0 Nm | 81.0 Nm |